

GRK Screw Selection Guide

GRK Climatek™ coated screws have been independently tested and approved for use in treated wood products. For best performance in exterior applications use PHEinox™ stainless steel screws.

GRK fasteners come with a limited Lifetime Warranty.

Pressure Treated Timber Decking:

Use 4.5 or 5.0 gauge R4™ on deck boards. For Southern Yellow Pine use 5.0. For best performance use PHEinox™ stainless steel screws.

Western Red Cedar Decking:

Use 4.5 or 5.0 gauge GRK R4™ to lock wood in place. For best performance use PHEinox™ stainless steel screws.

Ipe Decking:

Use 4.0 gauge PHEinox™ stainless steel Finishing Trim™ Head Screw. Pre-drilling is recommended with hardwood due to movement in the wood.

Composite & Plastic Decking:

For best performance use PHEinox™ RT Composite™ stainless steel screws.

Deck Joists & Structural Members :

For exceptional strength use RSS™ Structural Screws as a alternative to lag screws.

Pools, Hot Tubs, Saunas:

Use only PHEinox™ stainless steel screws by GRK.

**No pre-drilling for R4™, RSS™ and Trim™ Head screws
except where wood limitations require.**

GRK Fasteners utilises strict quality control procedures. Every batch of screws produced is independently random sampled and quality controlled to the highest standards.

Accreditations for independent test laboratories include:
ISO, ICC, CNLA, TÜV, DAR, Ü